

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

E. edges; from which

A Fir, 48 ins. diam., bears N.23*E., 168 lks. dist.,
marked T 32 S R 4 W S 21 B T.

A dead Fir, 30 ins. diam., bears S.33*E., 89 lks.
dist., marked T 32 S R 4 W S 28 B T.

A dead Fir, 36 ins. diam., bears S.22*W., 128 lks.
dist., marked T 32 S R 4 W S 29 B T.

A Fir, 30 ins. diam., bears N.23*W., 165 lks. dist.,
marked T 32 S R 4 W S 20 B T.

This corner is on the E. slope of ridge, about 75 ft.
below top.

Land, mountainous.

Soil, third and fourth rate.

Timber, scattering fir, hemlock, and madrona.

Dense undergrowth of mountain-balm and rhododendron.

Mountainous land or covered with dense undergrowth,

80.00 chs.

Thence, I run

East, on a random line, bet. secs. 21 and 28.

40.00 Set a temp. $\frac{1}{4}$ sec. corner.

79.86 Intersect N. and S. line, 10 lks. N. of corner of secs.
21, 22, 27 and 28.

Thence, I run

North, 89*56'W., on a true line bet. secs. 21 and 28.

Asc. spur.

8.25 Top of spur, slopes NW. 50 ft. above sec. corner.

Trail, bears N. and SE; desc.

30.10 Boulder Creek, 6 lks. wide, C. NW., 200 ft. below top
of last spur; asc. spur.

39.93 Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in
the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on N. face;
from which