

Subdivisions, T. 32 S., R. 4 W.

CHAINS

- 14.50 Top of spur, slopes E., 25 ft. above last ravine; desc.
- 18.00 Ravine, C. NE., 75 ft. below last spur; asc. spur.
- 22.50 Top of spur, slopes NE., 25 ft. above last ravine; desc.
- 26.50 Ravine, C. NE., 25 ft. below top of spur.
- 30.00 Enter Hogum Creek bottom, bears NW. and SE., 50 ft. below ravine. Foot of descent.
- 33.08 Hogum Creek, 8 lks. wide, C. NW.
- 38.08 Fizzleout Creek, 8 lks. wide, C. W., begin ascent.
- 38.74 Wagon road, bears NW. and SE.
- 40.00 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W., face, from which
- A Fir, 6 ins. diam., bears S.58*E., 33 lks. dist., marked $\frac{1}{4}$ S B T.
- A Fir, 48 ins. diam., bears N.70*W., 90 lks. dist., marked $\frac{1}{4}$ S B T.
- This $\frac{1}{4}$ sec. corner is on a S. slope, 25 ft. above creek.
- 43.96 Trail, bears E. and W.
- 52.00 Leave green timber, bears E. and W.
- 63.50 Top of spur, slopes SW., 300 ft. above creek; desc. Enter green timber, bears NE. and SW.
- 71.00 Ravine, C. SW. 50 ft. below top of spur; asc.
- 80.00 Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for a corner of secs. 16, 17, 20 and 21, marked T 32 S S 16 on NE., R 4 W S 21 on SE., S 20 on SW., and S 17 on NW. faces, with 4 notches on E. and 3 notches on S. edges; from which
- A Madrona, 8 ins. diam., bears N.27*E., 41 lks. dist., marked T 32 S R 4 W S 16 B T.
- A live Oak, 6 ins. diam., bears S.68*E., 27 lks. dist., marked T 32 S R 4 W S 21 B T.