

Subdivisions, T. 32 S., R. 4 W.

CHAINS

Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W. face, from which

A Fir, 12 ins. diam., bears S.50°E., 116 lks. dist., marked $\frac{1}{4}$ S B T.

A Madrona, 6 ins. diam., bears N.72°W., 88 lks. dist., marked $\frac{1}{4}$ S B T.

80.19 To a point, 39 lks. W. of the corner of secs. 7, 8, 17 and 18 which is a post 24 ins. above ground, marked and witnessed as described by the surveyor general. Therefore this line bears S.0°16'E.

Thence, I run

South, on a blank line, on E. bdy. of sec. 18.

40.12 To a point, 40 lks. W. of $\frac{1}{4}$ sec. corner, which is a post 24 ins. above ground, marked and witnessed as described by the surveyor general.

80.32 To a point, 84 lks. dist. W. of the corner of secs. 17, 18, 19 and 20, which is a post 24 ins. above ground, 4 ins. sq., marked and witnessed as described by the surveyor general.

Therefore, this line bears S.0°36'E.

September 7, 1897.

At the corner of secs. 29, 30, 31 and 32.

Thence, I run

South, 0°4'E. on a true line bet. secs. 31 and 32.

Desc.

6.46 Creek, 1 lk. wide, C. N.80°W., 100 ft. below sec. corner; asc. spur.

9.75 Top of spur, slopes W. 50 ft. above last creek; desc.

23.95 Creek, 4 lks. wide, C. NW., 100 ft. below top of last spur; asc. spur.

26.00 Leave green timber, bears E. and W.

40.00 Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W. face;