

## Subdivisions, T. 32 S., R. 4 W.

CHAINS	
	North, $0^{\circ}4'W.$ , on a true line, bet. secs. 29 and 30. Asc.
7.00	Top of ridge, bears NW. and SE. 100 ft. above sec. corner. Descend.
22.50	Spur, slopes NE., 75 ft. below top of ridge.
40.00	Set a yew post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W. face, from which A Fir, 8 ins. diam., bears $N.66^{\circ}E.$ , 10 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 20 ins. diam., bears $S.68^{\circ}W.$ , 64 lks. dist., marked $\frac{1}{4}$ S B T. This corner is on the NW. slope of spur, 200 ft. below top.
40.75	Ravine, C. W., 25 ft. below $\frac{1}{4}$ sec. corner; asc. spur.
42.00	Top of spur, slopes W., 35 ft. above ravine; desc.
48.97	Creek, 1 lk. wide, C. $N.10^{\circ}W.$
50.04	Creek, 1 lk. wide, C. $N.80^{\circ}W.$ , 100 ft. below top of last spur; asc. spur.
55.75	Top of spur, slopes SE., 50 ft. above last creek; desc.
57.45	Creek, 1 lk. wide, C. $S.30^{\circ}E.$ , 50 ft. below top of last spur; asc. spur.
62.50	Top of spur, slopes SE., 75 ft. above last creek; desc.
72.02	Creek; 2 lks. wide, C. $S.10^{\circ}E.$ , 25 ft. below top of last spur. Ascend spur.
80.00	Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for a corner of secs. 19, 20, 29 and 30, marked T 32 S S 20 on NE., R 4 W S 29 on SE., S 30 on SW., and S 19 on NW. faces; with 2 notches on S. and 5 notches