

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS	
5.53	Creek, 2 lks. wide, C. SE., 25 ft. below top of last spur, ascend spur.
9.75	Top of spur, slopes SE., 75 ft. above last creek; desc.
13.96	Creek, 1 lk. wide, C. SE., 50 ft. below top of last spur; asc.
17.75	Top of spur, slopes S., 75 ft. above creek; desc.
20.00	Ravine, C. S., 25 ft. below top of spur; asc.
25.00	Top of ridge, bears NE. and SW., 50 ft. above last ravine; descend.
30.75	Ravine, C. N., 75 ft. below top of ridge; asc. spur.
40.00	Set a fir post 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on N. face; from which <p data-bbox="406 1267 1409 1366">A Fir, 36 ins. diam., bears N.11*E., 132 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p data-bbox="406 1399 1393 1498">A Fir, 20 ins. diam., bears S.52*W., 88 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p data-bbox="354 1531 1377 1629">This corner is on the E. slope of spur, 100 ft. above ravine.</p>
46.00	Top of spur, slopes NE., 50 ft. above $\frac{1}{4}$ sec. corner; descend.
53.00	Ravine, C. N., 100 ft. below top of last spur; ascend spur.
60.25	Top of spur, slopes N., 75 ft. above last ravine; desc.
61.35	Ravine, C. N., 25 ft. below last spur; asc.
69.38	Intersect W. bdy. of Tp., 12.06 chs. N. of the corner of secs. 19, 30, 24 and 25, which is a post, 24 ins. above ground, marked and witnessed as described by the surveyor general. I reestablish this corner as follows: Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for corner of secs. 24 and 25, T 32 S R 5 W, marked