

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

T 32 S S 25 on SW., and R 5 W S 24 on NW. faces, with 2 notches on S. and 4 notches on N. edges; from which
 A Madrona, 5 ins. diam., bears S.11*W., 98 lks. dist., marked T 32 S R 5 W S 25 B T.

A Madrona, 5 ins. diam., bears N.7*W., 58 lks. dist., marked T 32 S R 5 W S 24 B T.

At point of intersection, 12.06 chs. N. of this corner,
 I

Set a chinquapin post 3 ft. long, 4 ins. sq., 24 ins. in the ground for a closing corner of secs. 19 and 30, marked

C C T 32 S R 4 W on E., S 19 on N., and S 30 on S. faces, with 2 grooves on S. and 4 grooves on N. faces; from which

A Madrona, 8 ins. diam., bears N.41*E., 27 lks. dist., marked T 32 S R 4 W S 19 B T.

A Madrona, 10 ins. diam., bears S.30*E., 30 lks. dist., marked T 32 S R 4 W S 30 B T.

This corner is on a N. slope, 100 ft. above ravine.

Land, mountainous.

Soil, third rate.

Timber, fir, madrona, yew, cedar and maple.

Dense undergrowth of madrona, hazel, fir, hemlock and ocean-spray.

Mountainous land, heavily timbered or covered with dense undergrowth, 69.38 chs.

From the corner of secs. 19, 20, 29 and 30, I run North, 0*4'W., on a true line, bet. secs. 19 and 20. Ascend spur.

3.00 Top of spur, slopes SE. 25 ft. above sec. corner; desc.

12.74 Creek, 2 lks. wide, C. SE., 100 ft. below top of last spur; asc. spur.