

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions, T. 32 S., R. 4 W.

## CHAINS

- 28.25 Top of spur, slopes E., 200 ft. above last creek; desc.
- 40.00 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  S on W. face; from which
- A Fir, 18 ins. diam., bears S.50\*E., 5 lks. dist., marked  $\frac{1}{4}$  S B T.
- A Fir, 16 ins. diam., bears S.23\*W., 14 lks. dist., marked  $\frac{1}{4}$  S BT.
- This corner is on N. slope of spur, 250 ft. below top.
- 44.18 Creek, 1 lk. wide, C. E., 325 ft. below top of last spur, asc. spur.
- 52.50 Top of spur, slopes E. 75 ft. above last creek; desc.
- 54.97 Creek, 1 lk. wide, C. N.70\*E., 50 ft. below top of last spur; asc. spur.
- 59.00 Top of spur, slopes E. 50 ft. above last creek; desc.
- 66.82 Creek, 1 lk. wide, C. N.30\*E., 75 ft. below top of spur.
- Ascend.
- 70.16 Intersect E. and W. line, 13.40 chs. S., 89\*4\*W. of the corner of secs. 17, 18, 19 and 20, which is a post 24 ins. above ground, marked and witnessed as described by the surveyor general.
- Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for a closing corner of secs. 19 and 20, marked C C T 32 S R 4 W on S., S 20 on E., and S 19 on W. faces, with 3 grooves on S. and 5 grooves on E. faces; from which
- A Fir, 36 ins. diam., bears S.76\*E., 41 lks. dist., marked T 32 S R 4 W S 20 B T.
- A Fir, 8 ins. diam., bears S.45\*W., 51 lks. dist., marked T 32 S R 4 W S 19 B T.
- This corner is on a NE. slope, 50 ft. above creek.