

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 4 W.

CHAINS

From the corner of secs. 8, 9, 16 and 17, I run South, $89^{\circ}53'W.$ on a true line bet. secs. 8 and 17. Descend.

- 6.75 Ravine, C. S., 75 ft. below sec. corner; asc. spur.
- 11.00 Top of spur, slopes S., 75 ft. above last ravine; desc.
- 34.75 Ravine, C. S. $30^{\circ}W.$, 175 Ft. below top of last spur.
- 38.25 Top of spur, slopes SW., 50 ft. above ravine; desc.
- 40.00 Set a fir post 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on N. face; from which
- A Madrona, 12 ins. diam., bears $N.15^{\circ}W.$, 11 lks. dist., marked $\frac{1}{4}$ S B T.
- A Madrona, 10 ins. diam., bears $S.8^{\circ}E.$, 7 lks. dist., marked $\frac{1}{4}$ S B T.
- This corner is on the SW. slope of spur, 50 ft. below top.
- 41.03 Creek, 1 lk. wide, C. S., 20 ft. below $\frac{1}{4}$ sec. corner; ascend.
- 57.25 Top of ridge, bears NE. and SW., 200 ft. above creek; descend.
- 62.75 Ravine, C. N., 75 ft. below top of ridge; asc. spur.
- 66.00 Top of spur, slopes N., 50 ft. above ravine; desc.
- 67.50 Intersect N. and S. line at a point which is $N.16^{\circ}W.$ of the corner of secs. 7, 8, 17 and 18, 9.77 chs. dist., I reestablish this corner as follows:
- Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for corner of secs. 7 and 18, marked T 32 S S 18 on SW., and R 4 W S 7 on NW. faces, with 4 notches on S. edge; from which
- An Oak, 5 ins. diam., bears $S.40^{\circ}W.$, 107 lks. dist., marked T 32 S R 4 W S 18 B T.
- An Oak, 30 ins. diam., bears $N.5^{\circ}W.$, 300 lks. dist., marked T 32 S R 4 W S 7 B T.