

# County Surveyor's Record, Douglas County, Oregon

8547

Offset West on South Bdy. of T. 32 S., R. 5 W.  
As surveyed by Butler Ives and Geo. W. Hyde, Dep. Surveyors  
Under Contract No. 39, dated January 4, 1854.

CHAINS	
	West, on South Bdy. of T. 32 S., R. 5 W.
	West, on South Bdy. of sec. 36.
	Va. 23°30'E.
2.75	Head of a stream, 1 lk. C. NW.
20.00	Top of a ridge. C. N.60°W., and commence descent on SW. slope.
20.00	Va. 18°30'E.
20.00	Latitude by compass, 42°44'.
40.00	Set qr. sec. post, from which
	A Y. Pine, 16 ins. diam., bears N.80°W., 118 lks.
	A Fir, 12 ins. diam., bears S.19½°E., 63 lks.
	Va. 18°10'E.
44.00	Ft. of SW. slope and descend gradually down S. slope.
71.50	Leave S. slope and begin to descend West slope.
77.18	A Y. Pine, 36 ins. diam.
80.00	Set post cor. of secs. 35, 36, 1 and 2, from which
	A Y. Pine, 20 ins. diam., bears N.61°W., 125 lks.
	A Y. Pine, 16 ins. diam., bears N.51°E., 71 lks.
	A Y. Pine, 20 ins. diam., bears S.47½°E., 102 lks.
	A Y. Pine, 24 ins. diam., bears S.47°W., 105 lks.
	Land, mountain slopes.
	Soil, 2nd. rate, red clay loam and stony.
	Timber, scattering Fir, Pine etc.
	Undergrowth, Laurel, Oak, Arrowwood, etc.
	West, on S. Bdy. of sec. 35.
	Va. 18°00
1.00	Foot of West slope of hill and enter valley.
	C. N.80°W. and SE.
36.90	A fir, 12 ins. diam.
36.90	Leave scattering timber and enter thick timber and brush.
40.00	Set qr. sec. post, from which
	A Laurel, 4 ins. diam., bears N., 12 lks.
	A Fir, 3 ins. diam., bears S.13°E., 19 lks.
	Va. 18°10'E.