

# County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 32 S., R. 5 W.,

CHAINS		
	about six miles E. of this township. This township contains about twelve settlers, the desirable location being mostly taken up.	
<hr/> <p>Subdivisions of T. 32 S., R. 5 W., As surveyed by W. H. Byars, Deputy Surveyor, Under Contract No. 152, dated June 3, 1871.</p> <hr/>		
	From the corner to secs. 2, 3, 34 and 35 on the S. bdy. of the township. I run N. bet. secs. 34 and 35.	
	Va. 19*E.	
40.00	Set $\frac{1}{4}$ sec. post, from which A Fir, 5 ins. diam. bears N.56*E., 16 lks. A Fir, 8 ins. diam. bears N.80*W., 14 lks.	-200
41.00	Leave dense and enter scattering timber.	-200
80.00	Set post cor. to secs. 26, 27, 34 and 35, from which A Fir, 36 ins. diam., bears N.10*E., 14 lks. A Pine, 24 ins. diam. bears S. 50*E., 26 lks. A Fir, 24 ins. diam., bears S.12*W., 68 lks. A Pine, 24 ins. diam. bears N.42*W., 76 lks.  Land level, 2nd rate.  Timber 2nd rate fir, pine, cedar, laurel, oak and maple, but little underbrush.	-300
<hr/>		
	E. on a true line bet. secs. 26 and 35.	
	Va. 19*E.	
9.50	A Creek, 25 lks. wide. C. N.	-25
35.50	Top of Spur. C. N.	+300
40.00	Set $\frac{1}{4}$ sec. post, from which A laurel, 24 ins. diam., bears N.70*E., 22 lks. A Pine, 36 ins. diam., bears S.10*E., 52 lks.	
72.00	A dry bed of creek, 10 lks. wide. NW.	00
74.00	Begin ascent.	00
80.00	Set post cor. to secs. 25, 26, 35 and 36, from which	+300