

County Surveyor's Record, ⁴⁴Douglas County, Oregon

Subdivisions of T. 32 S., R. 5 W.,

CHAINS

many items of interest were passed unobserved.

Subdivisional Lines, T. 32 S., R. 5 W.,
As surveyed by Oscar F. Thiel, Deputy Surveyor,
Under Contract No. 729, dated Dec. 24, 1900.

From the cor. of secs. 25, 26, 35 and 36, which being gone, I reestablish by setting a slate rock 18x16x4 ins. 12 ins. in the ground for cor. of secs. 25, 26, 35 and 36, marked with 1 notch on S. and E. edges, from which
A Live Oak, 10 ins. in diam. bears N.30*E., 33 lks.
Marked T 32 S. R. 5 W. S. 25 B. T.

A Live Oak, 8 ins. in diam. bears S.70*E., 10 lks.
Marked T 32 S. R. 5 W S 36 B.T.

A Live Oak, 8 ins. in diam. bears S.75*W., 22 lks.
Marked T 32 S. R. 5 W. S. 35 B. T.

A Live Oak, 8 ins. in diam. bears N.22*W., 23 lks.
Marked T 32 S R 5 W S 26 B. T.

I run

E., on a random line bet. secs. 25 and 36.

Over mountainous land, heavily timbered.

40.00 Set temp. $\frac{1}{2}$ sec. cor.

74.34 Intersect E. bdy. of Tp. 159 lks. N. of cor. of secs. 25, 30, 31 and 36, which is gone; I reestablish the cor. by setting a hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 25, 30, 31 and 36.

Marked T 32 S S 30 on NE.

R. 4 W S 31 on SE.

S. 36 on SW., and

R 5 W S 25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which

A Fir, 24 ins. diam. bears N.22*E., 86 lks.

Marked T 32 S R 4 W S 30 B. T. New B.T.

A Fir, 40 ins. diam. bears S.83*E., 12 lks.

Marked T 32 S R 4 W S 31 B T New B.T.