

46  
County Surveyor's Record, Douglas County, Oregon

Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

74.34  $\frac{1}{4}$  Sec. cor. Begin descent of steep SW. mountain slope covered heavily with burnt laurels and greasewood.  
The cor. of Secs. 25, 26, 35 and 36, 200 ft. below top of ridge.  
Land, mountainous.  
Soil, gravelly and rocky, 3rd and 4th rate.  
Timber, Fir, Cedar, Hemlock, Oak and Laurel, and Pine.  
Undergrowth, Arrowwood, Hazel, Small Firs and Hemlocks.  
Mountainous or heavily timbered land 74.34 chs. and connection 1.59 chs.  
July 18, 1901.

40.00 South, on a random line bet. Secs. 35 and 36.  
Over mountainous land, heavily timbered.  
Set temp.  $\frac{1}{4}$  Sec. cor.  
81.18 Intersect S. Bdy. of Tp. 5.44 chs. E. of cor. of Secs. 35, 36, 1 and 2, which is a sandstone 8x6x5 ins. above ground, marked with a notch on E., and 5 notches on W. edges, witnessed as described by the surveyor general, except  
A Y. Pine, 16 ins. diam., bears N.51\*E., 41 lks.  
Marked T 32 S R 5 W S 36 B T.  
The distance given by the surveyor general being 71 lks.  
a Y. Pine, 40 ins. diam. and marked with 2 notches on E. and W. sides, mentioned in the field notes, furnished by the surveyor general, stands W. from closing cor., 251 lks.  
I destroyed all marks, referring to Secs. 35 and 36, and at the point of intersection, I set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. of Secs. 35 and 36, marked C C T 32 S R 5 W on N., S 36 on E. and S 35 on W. faces, with 1 groove on E. and 5 grooves on W. faces, from which