

County Surveyor's Record, Douglas County, Oregon

Subdivisional Lines T 32 S., R. 5 W.,

CHAINS

Mountainous or heavily timbered land, 48.76 chs.
July 20, 1901

West on a random line bet. secs. 28 and 33.

Ascending mountain slope, heavily timbered.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.96 Intersect N. and S. line 21 lks. N. of cor. of secs. 28, 29, 32 and 33; the old cor. has disappeared and I reestablish the same by setting a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground (in mound of stone) marked T 32 S S 28 on NE., R 5 W S 33 on SE., S 32 on S W and S 29 on NW. faces; with 1 notch on S. and 4 notches on E. edges, from which

A Fir, 24 ins. diam. bears N.53*E., 27 lks.

Marked T 32 S R 5 W S 28 B T New B T

A Fir, 30 ins. diam. bears S.38*E., 19 lks.

Marked T 32 S R 5 W S 33 B T New B T

A Laurel, 12 ins. diam. bears S.20*W., 34 lks.

Marked T 32 S R 5 W S 32 B T Old B T

A Fir, 30 ins. diam. bears N.28*W., 38 lks.

Marked T 32 S R 5 W S 29 B T New B T

Thence I run

N.89*51'E. on true line bet. secs. 28 and 33.

Descend spur, heavily timbered.

3.25 A stream, 1 lk. wide. C. N., 30 ft. below sec. cor.

5.20 A stream, 1 lk. wide. C. N.

22.48 A Stream, 5 lks. wide. C. NW., 80 ft. below sec. cor.

Begin ascent of W. mountain slope.

25.00 Begin steep ascent of S. mountain slope.

39.00 Leave the large timber; keep on ascending.

40.00 Set a granite stone 18x12x6 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which

A Y. Pine, 40 ins. diam. bears N.68 $\frac{1}{2}$ *E., 113 lks.

Marked $\frac{1}{4}$ S 28 B T

A Bl. Oak, 28 ins. diam. bears S.72*E., 80 lks.

Marked $\frac{1}{4}$ S. 33 B T

This cor. stands 250 ft. above last stream.