

Subdivisional Lines T. 32 S., R. 5 W.,

CHAINS

connection line, 1.11 chs.

July 21, 1901.

At the cor. of secs. 28, 29, 32 and 33. Thence I run S.0*2'E. on a random line bet. secs. 32 and 33.

Ascend mountain slope, covered with dense undergrowth of small firs.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.47 Intersect S. bdy. of the Tp., 142 lks. W. of cor. to secs. 32, 33, 4 and 5, which is a granite stone 10x12x3 ins. above ground, marked as described by the surveyor general, from which

An Alder, 8 ins. diam. bears N.82*E., 23 lks.

Marked T 32 S. R. 5 W. S 33 B.T. Old B.T.

An Alder, 10 ins. diam. bears S.6*E., 38 lks.

Marked T. 33 S. R. 5 W. S. 4 B. T. New B.T.

A Fir, 50 ins. diam. bears S.51*W., 72 lks.

Marked T. 33 S R 5 W S 5 B. T. New B.T.

An Alder, 10 ins. diam. bears N.62*W., 8 lks.

Marked T. 32 S. R. 5 W. S. 32 B.T. Old B.T.

I destroyed all marks, referring to secs. 32 and 33, and at the point of intersection set a dogwood post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. of secs. 32 and 33, marked C. C. T. 32 S. R. 5

W. on N., S. 33 on E., and S. 32 on W. faces; with 4 grooves on E., and 2 grooves on W. faces, from which

A Fir, 72 ins. diam. bears N.61*E., 33 lks.

Marked T. 32 S. R. 5 W. S. 33 B.T.

A Maple, 10 ins. diam. bears N.9*W., 16 lks.

Marked T. 32 S. R. 5 W. S. 32 B.T.

Thence I run

N.0*2'W. on true line bet. secs. 32 and 33.

Descend slightly ft. of mountain slope, covered heavily with fir timber; bears E. and W.

3.20 A stream, 5 lks. wide, C. SW.; begin a steep ascent of