

Subdivisional Lines T. 32 S., R. 5 W.,

CHAINS

A Fir, 16 ins. diam. bears N.46\*E., 25 lks.  
 Marked T. 32 S. R. 5 W. S. 29 B.T. Old B.T.  
 A Dogwood, 4 ins. diam. bears S.67½\*E., 41 lks.  
 Marked T. 32 S. R. 5 W. S. 32 B.T. Old B. T.  
 A Maple, 11 ins. diam. bears S.87\*W., 29 lks.  
 Marked T. 32 S. R. 5 W. S. 31 B. T. New B.T.  
 A Wh. Fir, 12 ins. diam. bears N.21½\*W., 31 lks.  
 Marked T. 32 S. R. 5 W. S. 30 B. T. New B.T.

Thence I run

S.0\*2'E. on a random line bet. secs. 31 and 32.

Ascending NE. mountain slope, covered heavily by timber.

40.00 Set temp. ¼ sec. cor.

80.05 Intersect S. bdy. of Tp., 128 lks. W. of cor. of secs.

5, 6, 31 and 32, which is a quartzstone 8x10 ins.,  
 3 ins. above ground, marked and witnessed as described  
 by the surveyor general. I destroy the marks referring  
 to secs. 31 and 32, and at the point of intersection  
 I set a dogwood post, 3 ft. long, 4 ins. sq., 24 ins.  
 in the ground, for closing cor. of secs. 31 and 32,  
 marked T. 32 S. R. 5 W. on N., S. 32 on E., and S. 31  
 on W. faces with 5 grooves on E. and 1 groove on W.  
 faces; from which

A Fir, 36 ins. diam. bears N.43\*E., 57 lks.

Marked T. 32 S. R. 5 W. S. 32 B.T.

A Laurel, 10 ins. diam. bears N.38\*W., 32 lks.

Marked T. 32 S. R. 5 W. S. 31 B. T.

Thence I run

N.0\*2'W. on true line bet. secs. 31 and 32.

Descend N. mountain slope, covered heavily with timber.

18.00 Enter a dense V. maple thicket, bears E. and W.

20.60 A Stream, 5 lks. wide, C. NE., 100 ft. below sec. cor.,  
 begin ascent of S. mountain slope gradually.

26.50 Leave V. Maple thicket.