

## County Surveyor's Record, Douglas County, Oregon

## Subdivisional Lines T. 32 S., R. 5 W.,

CHAINS

- 32.80 A mountain trail, bears E. and W.
- 40.03 Set a fir post 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. 31 on W., and 32 on S. face, from which
- A Laurel, 9 ins. diam. bears N.24 $\frac{1}{2}$ \*E., 30 lks.  
Marked  $\frac{1}{4}$  S. 32 B.T.
- A Chincopin, 8 ins. diam. bears N.16\*W., 44 lks.  
Marked  $\frac{1}{4}$  S. 31 B.T.
- Continue ascent of S. mountain spur.
- 43.25 Top of spur, bears E. and W.; 175 ft. above stream.  
Begin steep descent.
- 49.40 Descent becomes more gradual.
- 66.50 The descent becomes steeper.
- 80.05 The cor. of secs. 29, 30, 31 and 32 is 260 ft. below top of spur.
- Land mountainous.
- Soil, loam and gravelly; 2nd and 3rd rate.
- Timber, fir, pine, cedar, laurel, maple, chincopin.
- Undergrowth, V. maple, hazel, arrowwood.
- Mountainous or heavily timbered land, 80.05 chs.  
connecting line, 1.28 chs.
- July 22, 1901.
- 
- At the cor. of secs. 3, 4, 9 and 10, which having disappeared, I replace, by setting a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked T. 32 S. S. 3 on NE., R. 5 W. S. 10 on SE., S. 9 on SW, and S. 4 on NW. faces with 5 notches on S. and 3 notches, on E. edges, and witnessed as described by the surveyor general. I run thence
- N.0\*1'W. on a random line bet. secs. 3 and 4.
- Ascend mountain slope, covered heavily with timber.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 78.45 Intersect N. bdy. of Tp. 42 lks. W. of cor. to secs.