

Retracement of Subdivisional Lines of T. 32 S., R. 5 W.,

CHAINS	
	W. bet. secs. 26 and 35.
	Descend a very steep and rocky SW. slope, covered with a dense undergrowth of small live oak.
7.50	A creek, 15 lks. wide. C. NW.; begin ascent, of NE. Mountain slope, covered heavily with large firs, pines and laurels.
37.70	The $\frac{1}{4}$ sec. cor.; the post having disappeared I set a laurel post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S. 26 on N. face, and 35 on S. face, from which <p style="margin-left: 40px;">A Laurel, 24 ins. diam. bears N.70*E., 22 lks. Marked $\frac{1}{4}$ S. 26 B.T.; original B.T. A Y. pine, 40 ins. diam. bears S.24*W., 133 lks. Marked $\frac{1}{4}$ S. 35 B.T. New bearing tree.</p> This cor. stands 225 ft. above creek; continue ascent of NE. slope.
40.70	Top of ridge, bears SE. and NW., 20 ft. above $\frac{1}{4}$ sec. cor., begin descent of W. slope, covered by scattering large pines, firs and laurels, and undergrowth of hazel, small firs and laurels.
63.70	Ft. of descent, 300 ft. below top of ridge, enter large fir and pine timber, bears N. and S.; a creek bottom.
67.75	Quine's Creek, 40 lks. wide, 1 ft. deep of pure water, C. N.,
74.00	A water ditch, C. N. to a private house, Tulett's.
75.45	A Wagon road, bears N. and S.; leave bottom, begin slight ascent.
77.75	The cor. of secs. 26, 27, 34 and 35; the old post having disappeared, I set a pine post, 3 ft. long, 4 ins. sq., with marked sandstone 12x12x10 ins., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked T. 32 S. S. 26 on NE., R. 5 W. S. 35 on SE., S. 34 on SW. and S. 27 on NW. faces; with 1 notch on S. and 2 notches on E. edges, and witnessed as described by the surveyor general, this cor. stands 15 ft. above creek. Land mountainous.