

72  
County Surveyor's Record, Douglas County, Oregon

Resurvey of Subdivisional Lines of Tp. 32 S., R. 5 W.

CHAINS 75.10	Top of ridge, about 350 ft. above dry bed of gulch, bears N. and S., steep desc. of E. slope.
79.99	C. cor. for secs. 27 and 28, bears S., 19 lks. about 60 ft. below summit of ridge.  Land, level and mountainous.  Soil, first and second rate.  44.95 chs. scattering timber, 35.04 chs. heavy timber.  True C. of this line is S.89*34'E.  <p style="text-align: right;">July 16, 1904.</p>
	At the cor. of secs. 35 and 36. Thence I run  East, bet. Secs. 1 and 36.  Gradual ascent of W. slope.
3.50	Change to SW. slope; ascend, scattering pine and fir timber.
34.64	Old $\frac{1}{4}$ Sec. cor. gone, I reestablished by setting a pine post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S 36 on N. face and S 2 on S. face, witnessed as described by the Surveyor General.  $\frac{1}{4}$ Sec. cor. stands about 800 ft. above the closing cor.
54.80	Top of spur about 350 ft. above the $\frac{1}{4}$ Sec. cor. bears NW. and SE., change to NE. slope.
72.00	Stream, 1 lk. wide, pure cold water, course NW. about 100 ft. below top of spur.  Ascend.
74.72	SE. cor. of Sec. 36, old post gone I reestablished this cor. by setting a basalt stone, 12x10x10 ins., 8 ins. in the ground, marked with 6 notches on the S. and W. edges, witnessed as described by the Surveyor General.  Land, very mountainous.  Soil, 3rd and 4th rate.  Timber, Fir, Pine and Hemlock.