

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 32 S., R. 7 W., as surveyed
by W. H. Byars, Deputy Surveyor, under Contract
No. 420, dated Sept. 16, 1881.

CHAINS

Marked T 32 S R 6 W S 31 B T.

A Fir, 8 ins. diam., bears S.57*W., 39 lks. dist.

Did not open old blazes.

A Fir, 36 ins. diam., bears N.24*W., 17 lks. dist.

Marked T 32 S R 7 W S 25 B T.

The sec. on E. having been surveyed I did not remove
old cor.

Land level for 22.50 chs, then hilly and rolling to cor.

Soil, sandy loam and gravel in bottom. 1st and 3rd.

rates. And clay and gravel on hill, 3rd. rate.

Timber chiefly Pine, Fir, Cedar, Laurel, Oak and Yew.

Under growth same with Hazel and Vine Maple.

North, between Secs. 25 and 30.

Va. 18*E

- 9.40 Creek, 12 lks. wide, course S.10*E
- 25.00 Begin ascent.
- 40.00 Unable to find old cor. or witness trees. Set a Cedar
post, 4 ft. long, 4 ins. sq., 18 ins. in ground.
Marked $\frac{1}{2}$ S on W. side for the $\frac{1}{2}$ sec. cor. from which
A Pine, 54 ins. diam., bears N.42*E., 76 lks. dist.
Marked, $\frac{1}{2}$ S B T.
A Fir, 8 ins. diam., bears West, 39 lks. dist.
Marked, $\frac{1}{2}$ S B T.
- 58.00 Top of spur, course S.20*W
- 71.50 Same, course S.10*E.
- 80.00 Old Cor. and witness trees destroyed. Set Chinquapin
post, 4 $\frac{1}{2}$ ft. long, 4 in sq., 20 ins. in ground for cor.
to secs. 19, 24, 25 and 30. Marked T 32 S R 6 W S 19,
on NE. face. T 30 on SE. face. S. 25 on SW. face
T 32 S R 7 W S 24 on NW face. Also two notches on S.
and 4 on the N. edges of same, from which
A Laurel, 6 ins. diam., bears N.85*E., 23 lks. dist.
Marked, T 32 S R 6 W S 19 B T.
A Fir, 30 ins. diam., bears S.15*E., 28 lks. dist.