

East Boundary of T. 32 S., R. 7 W., as Surveyed  
by W. H. Byars, Deputy Surveyor, under Contract  
No. 420, dated Sept. 16, 1881.

CHAINS

Marked, T 32 S R 6 W S 30 B T.

A Laurel, 8 ins. diam., bears S.10\*W., 38 lks. dist.

Marked T 32 S R 7 W S 25 B T.

A Laurel, 8 ins. diam., bears N. 20\*W., 44 lks. dist.

Marked, T 32 S R 7 W S 24 B T.

Land mountainous, sloping S.

3rd. rate soil clay and gravel.

Timber chiefly Fir, Pine, Cedar, Laurel and Oak.

North, between secs 19 and 24.

Va. 18\*E

11.00 Begin steep ascent.

38.00 Top of ridge, course S.20\*W., and N.20\*W.

40.00 Not being able to find old cor. or witness trees, set  
a Laurel post, 4 ft. long, 4 ins. diam., 20 ins. in  
ground. Marked  $\frac{1}{4}$  S.on W. side for the  $\frac{1}{4}$  sec. cor.,  
from which

A Fir, 36 ins. diam., bears S.48\*E., 45 lks. dist.

Marked  $\frac{1}{4}$  S B T.

A Fir, 38 ins. diam., bears N.52\*W., 30 lks. dist.

Marked  $\frac{1}{4}$  S B T.

65.00 Begin steep rocky ascent.

80.00 Not being able to find old cor. or witness trees I set  
a Fir post 4 $\frac{1}{2}$  ft. long, 4ins. sq. 22 ins. in ground  
for the cor. to secs. 13, 18, 19 and 24. Marked  
T 32 S R 6 W S 18 on NE face. S 19, on SE. face.  
S 24, on SW. face. T 32 S R 7 W S 13 on NW. face.  
3 notches on the S. and 3 on the N. angles of same,  
from which

A Laurel, 8 ins. diam., bears N.85\*E., 30 lks. dist.

Marked T 32 S R 6 W S 18 B T.

A Laurel, 6 ins. diam., bears S. 30\*E., 61 lks.  
dist.

Marked T 32 S R 6 W S 19 B T.

A Pine, 24 ins. diam., bears S.70\*W., 100 lks. dist.