

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 32 S., R. 7 W., as surveyed
by W. H. Byars, Deputy Surveyor, under Contract
No. 420.. dated Sept. 16, 1881.

CHAINS

Marked T 32 S R 7 W S 24 B T.

A Live Oak, 5 ins. diam., bears N.45*W., 31 lks. dist.

Marked T 32 S R 7 W S 13 B T.

Land, high mountainous..

Soil, rocky gravelly, 4th rate.

Timber chiefly Pine, and Fir, poor. Under growth of same.

Live Oak, Balm and "Mansaneta" very dense.

North, between sefs. 13 and 18.

Va. 18*E

Continue steep ascent.

13.00 Rocky ledge, course N.15*E. Leave timber.

32.00 Top of high mountain. Begin steep rocky descent.

36.00 Gradual descent.

40.00 Set Cedar post 4 ft. long, 4 ins. sq., marked $\frac{1}{2}$ S on W.
side, 18 ins. in ground for the $\frac{1}{2}$ sec. cor., from which

A Fir, 24 ins. diam., bears S.22*E., 50 lks. dist.

Marked $\frac{1}{2}$ S B T.

A Fir, 30 ins. diam., bears S.35*W., 37 lks. dist.

Marked $\frac{1}{2}$ S B T.

52.00 Steep descent, center green timber.

65.50 Moderate descent.

75.00 Steep descent.

80.00 Set a Cedar post for the cor. secs. 7, 12, 13 and 18,
viz: 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 22 ins. in ground and
marked T 32 S R 6 W S 7 on SE, face. S 18, on SE.
face. S 13, on SW. face. T 32 S R 7 W S 12 on NW face.
Also 4 notches on S. and 2 on both angles of same,
from which

A Fir, 44 ins. diam., bears N.10*E., 31 lks. dist.

Marked T 32 S R 6 W S 6 B T.

A Fir, 24 ins. diam., bears S.8*E., 18 lks. dist.

Marked T 32 S R 6 W S 18 B T.