

East Boundary of T.32 S., R. 7 W., as surveyed
by W. H. Byars, Deputy Surveyor, under Contract
No. 420, dated Sept. 16, 1881.

CHAINS

A Fir, 10 ins. diam., bears S. 12*W., 31 lks. dist.

Marked T 32 S R 7 W S 13 B T.

A Fir, 15 ins. diam., bears N.63*W., 71 lks. dist.

Marked T 32 S R 7 W S 12 B T.

Land broken, mountainous.

Soil rocky, 4th. rate.

Timber inferior Fir, Pine and Cedar. ✓

Oct. 22, 1881

North, between Secs. 7 and 12.

Va. 18*E

Continue steep descent.

10.25 Creek, 6 lks. wide, course NW.

24.00 Top of spur, course NW. Descend.

40.00 Set a fir post 4 ft. long, 4 ins. sq., 20 ins. in the
ground. Marked $\frac{1}{4}$ S. on W. side for the $\frac{1}{4}$ sec. cor.,
from which

A Fir, 24 ins. diam., bears N.55*E., 12 lks. dist.

Marked $\frac{1}{4}$ S B T.

A Laurel, 10 ins. diam., bears S.70*W., 29 lks.
dist.

Marked $\frac{1}{4}$ S B T.

42.40 Creek, 4 lks. wide, course NW.

80.00 Set a fir post 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 22 ins. in the
ground, for the cor. to secs. 1, 6, 7 and 12. Marked
T 32 S R 6 W S 6 on NE. face. S 7 on SE. face. S 12
on SW, face. T 32 S R 7 W S 1 on NW. face. Also 5
notches on S. and one notch on N. angles of same,
from which

An Alder, 8 ins. diam., bears N.45*E., 58 lks. dist.

Marked T 32 S R 6 W S 6 B T.

An Alder, 12 ins. diam., bears S.55*E., 52 lks. dist.

Marked T 32 S R 6 W S 7 B T.

A Fir, 30 ins. diam., bears S.65*W., 23 lks. dist.

Marked T 32 S R 6 W S 12 B T.