

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S. R. 6 W.

CHAINS

A B. Oak, 12 ins. diam., bears S.39*W., 102 lks. dist.,
marked T 32 S R 6 W S 28 B T.

A B. Oak, 10 ins. diam., bears N.61*W., 121 lks. dist.,
marked T 32 S R 6 W S 21 B T.

I run North between secs. 21 and 22.

Va19*30'E

40.00 Set a Pine post 3 ft. long, 3 ins. sq., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S. on W. face, from
which

A Fir, 60 ins. diam., bears N.35*E., 40 lks. dist.,
marked $\frac{1}{4}$ S B T.

A Fir, 72 ins. diam., bears S.80*W., 11 lks. dist.,
marked $\frac{1}{4}$ S B T.

55.00 Steep rocky ascent.

80.00 Set an Oak post 4 ft. long, 4 ins. sq., 24 ins. in the
ground, for cor. to secs. 15, 16, 21 and 22, marked
T 32 S R 6 W S 15 on NE. S 22 on SE. S 21 on SW.,
and S 16 on NW., faces with 3 notches on S. and E.
edges, from which

A Cedar, 40 ins. diam., bears N.89*E., 6 lks. dist.,
marked T 32 S R 6 W S 15 B T.

A Cedar, 30 ins. diam., bears S.55*E., 38 lks. dist.,
marked T 32 S R 6 W S 22 B T.

A Laurel, 4 ins. diam., bears S.42*W., 20 lks. dist.,
marked T 32 S R 6 W S 21 B T.

A Chinquapin, 12 ins. diam., bears N.5*W., 20 lks.
Dist., marked T 32 S R 6 W S 16 B T.

Land, South part hilly, 2nd rate. North, part broken and
rocky, 3rd rate.

Timber, Fir, Pine, Cedar, Laurel, Chinquapin and Oak.

Undergrowth same.

East, on random line between secs. 15 and 22.

Va. 19*30'E

Begin steep descent.

40.00 Set temp. $\frac{1}{4}$ sec. cor