

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 6 W.

CHAINS

An Alder, 8 ins. diam., bears N.45*E., 58 lks. dist.
marked T 32 S R 6 W S 6 B T.

An Alder, 12 ins. diam., bears S.55*E., 52 lks.
dist., marked T 32 S R 6 W S 7 B T.

A Fir, 30 ins. diam., bears S.65*W., 23 lks. dist.,
marked T 32 S R 7 W S 12 B T.

A Fir, 6 ins. diam., bears N.48*W., 9 lks. dist.,
marked T 32 S R 7 W S 1 B T.

Thence S.89*44'E true line between secs. 6 and 7.
on
^

Va.19*E

45.40 Set a Laurel post 3 ft. long, 3 ins. sq., 24 ins. in the
ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face, from
which

A Pine, 18 ins. diam., bears N.10*E., 54 lks. dist.,
marked $\frac{1}{4}$ S B T.

A Laurel, 14 ins. diam., bears S.45*W., 4 lks. dist.,
marked $\frac{1}{4}$ S B T.

85.40 The cor. to secs. 5, 6, 7 and 8.

Land on NW. slope of mountain, soil 3rd. rate.

Timber, Fir, Pine, Laurel, Cedar and Chinquapin.

Undergrowth same.

November 22, 1881.

North on random line between secs. 5 and 6.

Va.17*45'E

Along mountain side facing W.

15.00 Steep descent to

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. boundary of township 180 lks. East of cor.
to secs. 5, 6, 31 and 32, which is a post 4 ins. sq.,
firmly set in the ground and marked T 31 S R 6 W S 32
on NE. T 32 S R 6 W S 5 on SE. S 6 on SW and S 31 on
NW. faces with 5 notches on E. and 1 notch on W. edges,
from which

A Laurel, 12 ins. diam., bears N.78*E., 70 lks. dist.,