

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 6 W.

CHAINS

marked T 31 S R 6 W S 32.

A Fir, 10 ins. diam., bears S.64°E., 58 lks. dist.,

marked T 32 S R 6 W S 5 B T.

A Laurel, 6 ins. diam., bears S.35°W., 53 lks. dist.,

marked T 32 S R 6 W S 6 B T.

A Laurel, 8 ins. diam., bears N.37°W., 98 lks. dist.,

marked T 31 S R 6 W S 31 B T.

Thence S.1°17'E on true line between secs. 5 and 6.

Va. 19°E

39.90 Set a Cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which

A Maple, 5 ins. diam., bears N.40°E., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.

A Fir, 28 ins. diam., bears N.54°W., 18 lks. dist.,
marked $\frac{1}{4}$ S B T.

79.90 The cor. to secs. 5, 6, 7 and 8.

Land mountainous.

Soil 3rd. rate.

Timber, Fir, Pine, Cedar, Laurel, and Chinquapin.

Undergrowth same.

November 23, 1881.

General Description

This township is generally mountainous. Very broken in the North part, with small valleys along the small streams. It is chiefly valuable for the timbers which are generally good. Chiefly Fir, Pine, Cedar, Oak, Laurel and Yew.

Several settlements are already made in secs. 22, 23 and 26.

William H. Byars

U. S. Deputy Surveyor.