

County Surveyor's Record, Douglas County, Oregon

7th Standard of Tp. 32 S., R 7 West.

CHAINS

A Pine, 28 ins. diam., bears N.57*E., 50 lks.

dist. marked S C T 32 S R 7 W S 31 B T.

A Pine, 36 ins. diam., bears N.20*W., 80 lks.

dist. marked S C T 32 S R 8 W S 36 B T.

A Fir, 34 ins. diam., bears S.20*E., 62 lks.

dist. marked S C T 33 S R 8 W S 1 B T.

Land, high mountainous.

Soil, clay rocky 3rd rate.

Timber, chiefly Pine, and Fir,

Thick undergrowth of same and Live Oak, Balm and Laurel.

October 18th, 1881.

This line extends along down the basin of Cow Creek, which is here confined to a very narrow valley and in many places to a rocky canyon. The hills or mountains on each side are very high generally covered with a good class of timber chiefly Pine, Fir, and Cedar. There are several settlements along the line. Also considerable placer mining is and has been done along the main creek and its tributaries.

Exteriors of Tp.32 S., R 7 W
same Deputy and Contract.

I begin at the standard corner to Tps. 32 S Ranges 7 and 8 West, which is a post, 4½ feet long 4 ins. sq., marked S C T 32 S on N R 7 W S 31 on E and R 8 W S 36 on W faces, with six notches on NE and W faces, from which;

A Pine, 28 ins. diam., bears N.57*E., 50 lks. dist.

A Pine, 36 ins. diam., bears N.20*W., 80 lks. dist.

A Fir, 34 ins. diam., bears S.20*E., 62 lks.

Thence I run

North between Secs. 31 and 36.

Va.18*E