

Exteriors of Tp. 32 S., R 7 W.

CHAINS

to be 4 chains and 20 lks. South of corner to Tps. 31, and 32, S Rs 6 and 7 W This being greatly in excess of limits allowed I proceed to an examination of the East boundary of T 32 S R 7 W.

October 20th, and 21st 1881.

Subdivisions of Tp. 32 S. R 7 W
Same Deputy and Contract.

I commenced at the cor. to secs. 35 and 36 on the South boundary, thence North between Secs. 35 and 36.

Va. 18°30'E

- 5.00 Cow Creek, 140 lks. wide course SW
- 12.18 Wagon Road course W
- 15.00 Begin ascent leave valley.
- 30.00 Spring branch 1 lk wide course S 20°E.
- 40.00 Set A Pine post, 4 feet long 5 ins. diam., 18 ins. in the ground, marked $\frac{1}{4}$ S on W side for the $\frac{1}{4}$ Sec. Cor. from which;
 - A Pine, 36 ins. diam., bears S.45°E., 24 lks. dist. marked $\frac{1}{4}$ S B T.
 - A Pine, 40 ins. diam., bears S.28°W., 20 lks. dist. marked $\frac{1}{4}$ S B T.
- 61.00 Top of Spur, course SW.
- 71.50 Spring, course W
- 80.00 Set A Cedar post, 4 feet long 4 ins. sq., 18 ins. in the ground for corner to Sections 25, 26, 35, and 36.
 - marked T 32 S R 7 W S 25 on NE side, S 36 on SE side, S 35 on SW side S 26 on NW side, with one notch on S and E edges of same, from which;
 - A Pine, 15 ins. diam., bears N.45°E., 50 lks. dist. marked T 32 S R 7 W S 25 B T.
 - A Fir, 18 ins. diam., bears S.5°E., 51 lks. dist. marked T 32 S R 7 W S 36 B T.
 - A Fir, 16 ins. diam., bears S.6°W., 55 lks. dist. marked T 32 S R 7 W S 35 B T.
 - A Fir, 20 ins. diam., bears N.20°W., 17 lks. dist. marked T 32 S R 7 W S 26 B T.

Land, level in valley otherwise mountainous.

Soil, sandy loam 2nd rate in valley otherwise clay and gravel 3rd rate.

Timber chiefly Fir, Pine, Cedar, and Laurel.

Underbrush same, with Vine Maple in valley.