

Retracement of the 7th Standard Parallel  
South through Range 7 West.

CHAINS

S C  $\frac{1}{4}$  S 32 on N face, and 5 on S face, from which;  
An Alder, 4 ins. diam., bears N.28\*W., 21 lks.  
dist. marked S C  $\frac{1}{4}$  S 32 B T. new B T.  
A Fir, 30 ins. diam., bears S.20\*W., 20 lks.  
dist. marked S C  $\frac{1}{4}$  S B T. original B T.

This cor. stands 250 ft.. above creek 10 lks. wide.  
A Cabin stands S of Cor. 33 lks. continue ascent of  
E slope.

56.25 The ascent becomes steeper.

69.05 The closing cor. of Secs. 5 and 6 on N slope of  
mountain, 300 ft. above  $\frac{1}{4}$  Sec. Cor.

Land, mountainous.

Soil, gravelly and 3rd rate.

Timber, Fir, Pine, Cedar, and Laurel.

Undergrowth, small Live and Burr Oak, Chinquapin.

Whole line of Sec. 5, 10.82 + 69.05 = 79.87 Chs.

West between Sec. 6 and 32

Ascending N slope of mountain, covered with timber,  
bears N and S

9.15 The Standard Cor. of Secs. 31 and 32 80 ft. above  
closing cor. continue to ascend.

Thence I run

West, between Sec. 6 and 31

10.00 Top of Spur, bears N and S 200 ft. above closing cor.  
begin descend of N slope, covered with burnt timber,  
bears N and S

39.23  $\frac{1}{4}$  Sec. Cor. which, having disappeared, I set a granite  
stone 12x10x10 ins. 8 ins. in the ground for  
standard  $\frac{1}{4}$  Sec. Cor. marked S C  $\frac{1}{4}$  on N face, and  
witnessed as described by the surveyor general. This  
Cor. stands 300 ft. below top of spur and 30 lks.  
N of a Bluff 20 ft. high; continue descend of steep  
N slope.