

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 8 W.

CHAINS	
	<p>Marked $\frac{1}{4}$ S B T.</p>
80.23	<p>The cor. to secs. 11, 12, 13, and 14. Land, steep, broken, and mountainous. Soil, clay, 3rd rate. Timber, chiefly Fir, Pine. Undergrowth, thick of Laurel, Balm, Chinquapin, and Huckleberry.</p> <p style="text-align: right;">June 20, 1883.</p>
	<p>North between Sections 11 and 12.</p>
	<p style="text-align: right;">Va. 19°45'E.</p>
8.00	<p>Top of spur, course NE. Descent.</p>
40.00	<p>A Laurel, 5 ins. diam., which I mark $\frac{1}{4}$ S on W side for the $\frac{1}{4}$ sec. cor., from which A Laurel, 5 ins. diam. bears N. 10°E., 10 lks. dist. Marked $\frac{1}{4}$ S B T. A Laurel, 5 ins. diam., bears N. 14°W., 9 lks. dist. Marked $\frac{1}{4}$ S B T.</p>
71.00	<p>West fork of Cow Creek 100 lks. wide, course NE.</p>
80.00	<p>Set a Laurel post 4 ft. long, 4 ins. sq., 24 ins. in the ground for the cor. to secs. 1, 2, 11, and 12. Marked T 32 S R 8 W S 1 on NE face. S 12 on SE face; S 11 on SW and S 2 on the NW faces, also 5 notches on the S and 1 notch on the E angles of the same and from which A Laurel, 12 ins. diam., bears N. 40°E., 55 lks. dist. Marked T 32 S R 8 W S 1 B T. A Laurel, 10 ins. diam., bears S. 30°E., 36 lks. dist. Marked T 32 S R 8 W S 12 B T. A Fir, 30 ins. diam., bears S. 20°W., 66 lks. dist. Marked T 32 S R 8 W S 11 B T. A Fir, 24 ins. diam., bears N. 40°W., 57 lks. dist. Marked T 32 S R 8 W S 2 B T.</p>