

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 32 S., R. 8 W.

CHAINS  
80.00

Set a Fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for the cor. to Secs. 22, 23, 26, and 27 and marked T 32 S R 8 W S 23 on NE, S 26 on SE, S 27 on SW, and S 22 on NW faces, also 2 notches on the S and 2 notches on the East angle of same, and from which

An Alder, 8 ins. diam., bears N.20\*E., 28 lks. dist., marked T 32 S R 8 W S 23 B T.

An Alder, 10 ins. diam., bears S.50\*E., 33 lks. dist., marked T 32 S R 8 W S 26 B T.

A Fir, 10 ins. diam., bears S.35\*W., 18 lks. dist., marked T 32 S R 8 W S 27 B T.

A Maple, 10 ins. diam., bears N.12\*W., 44 lks. dist., marked T 32 S R 8 W S 22 B T.

Land, mountainous.

Soil, rocky, 4th rate.

Timber, dense, chiefly Fir, Pine, Laurel, Cedar &amp; Yew.

Undergrowth, thick, Laurel, Live Oak, Fir, Balm and Huckleberry.

June 22, 1883.

East, on random line between Secs. 23 and 26.

Va. 19\*45'E.

0.30 A Creek, 3 lks. wide, course SE. Ascent.

16.00 Top of spur. Course S.

27.85 A Creek, 3 lks. wide, course South.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

48.00 A Creek, 2 lks. wide, course SE.

53.00 Same creek, course N.95\*E.

61.00 Same creek, course S.70\*E.

78.00 A Creek, 30 lks. wide, course NE.

80.30 Intersect N and S line, 42 lks. S of the cor. to Secs. 23, 24, 25, and 26. Thence I run. S.89\*42'W. on true line between Secs. 23 and 26.

Va. same.

40.15 Set a Chinquapin post, 3 ft. long, 3 ins. sq., 20 ins.