

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 8 W.

CHAINS	
	<p>A Laurel, 7 ins. diam., bears S.36*E., 16 lks. dist.  Marked <math>\frac{1}{4}</math> S B T.</p>
79.86	<p>The cor. to secs. 19, 20, 29, and 30.  Land, mountainous and broken.  Soil, 3rd rate.  Timber, chiefly Fir, Pine, and Laurel.  Undergrowth, thick of Laurel, Fir, Balm, Live Oak, and  Chinquapin.</p>
	<p>West, on random line between secs. 19 and 30.  Va. 19*45'E.</p>
24.00	<p>Top of spur, course North. Descend NW slope.</p>
40.00	<p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
48.00	<p>A creek, 2 lks. wide, course North. Steep ascent.</p>
55.00	<p>Rocky North slope.</p>
70.00	<p>A creek, 2 lks. wide, course N.60*E. Ascend to</p>
79.83	<p>Intersect W bdy. of tp. 60 lks. North of the cor. to secs.  19, 24, 25, and 30, which is a stone firmly set in the  ground marked with two notches on the S and four notches  on the N, and from which</p>
	<p>A Laurel, 10 ins. diam., bears N.13*E., 46 lks. dist.  Marked T 32 S R 8 W S 19 B T.</p>
	<p>A Fir, 10 ins. diam. bears S.78*E., 16 lks. dist.  Marked T 32 S R 8 W S 30 B T.</p>
	<p>A Fir, 18 ins. diam., bears S.64*W., 20 lks. dist.  Marked T 32 S R 9 W S 25 B T.</p>
	<p>A Sugar Pine, 24 ins. diam. bears N.51*W., 45 lks. dist.  Marked T 32 S R 9 W S 24 B T.</p>
	<p>Thence I ran.</p>
	<p>N.89*34'E. on a true line between secs. 19 and 30.  Va. same.</p>
39.92	<p>Set a stone 12x10x8 ins., 8 ins. in the ground marked  <math>\frac{1}{4}</math> on N side for the <math>\frac{1}{4}</math> sec. cor., and from which  A Laurel, 14 ins. diam., bears S.75*W., 35 lks. dist.,  marked <math>\frac{1}{4}</math> S B T.</p>