

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 32 S., R. 8 W.

CHAINS

- 72.00 Top of high spur, course NE. Steep descent.
- 80.00 Set a stone 16x12x8 ins., 12 ins. in the ground marked with five notches on the S and E angles of same for the cor. to secs. 5, 6, 7, and 8, and from which
- A Laurel, 8 ins. diam., bears N.85°E., 32 lks. dist.  
Marked T 32 S R 8 W S 5 B T.
- A Laurel, 6 ins. diam., bears S.26°E., 21 lks. dist.  
Marked T 32 S R 8 W S 8 B T.
- A Fir, 30 ins. diam., bears S.40°W., 31 lks. dist.  
Marked T 32 S R 8 W S 7 B T.
- A Fir, 50 ins. diam., bears N.25°W., 14 lks. dist.  
Marked T 32 S R 8 W S 6 B T.
- Land, mountainous.  
Soil, rocky, 3rd rate.  
Timber, densely covered, chiefly Fir, Pine, and Laurel.  
Undergrowth, thick, Laurel, Fir, Live Oak, Balm, and Chinquapin.
- 
- East on a random line between secs. 5 and 8.  
Va. 19°45'E.
- 7.50 Top of spur, course NE. Descend.
- 40.00 Set temp  $\frac{1}{4}$  sec. cor.
- 63.00 A creek, 2 lks. wide, course SE.
- 77.50 (West Fork), 100 lks. wide, course South.
- 79.42 Intersect N and S line, 77 lks. S. of cor. to secs. 4, 5, 8, and 9. Thence I ran.  
S.89°27'W., on a true line between secs. 5 and 8.  
Va. same.
- 39.71 Set a Laurel post 3 ft. long, 3 ins. sq., 20 ins. in the ground marked  $\frac{1}{4}$  S on N side for the  $\frac{1}{4}$  sec. cor. from which
- A Laurel, 10 ins. diam., bears S.85°W., 10 lks. dist.  
Marked  $\frac{1}{4}$  S B T.
- A Laurel, 10 ins. diam., bears N.85°W., 11 lks. dist.