

Resurvey East bdy. of T. 32 S., R. 9 W.  
As surveyed by Fred Mensch and Gerald A. Sorrels, Deputy  
Surveyors, under special instructions dated Dec. 22, 1916.

CHAINS

Retracements

From the standard cor. of Tps. 32 S., Rs 8 and 9 W., North retracing E. bdy. of sec. 36; at 39.56 chs. the  $\frac{1}{4}$  sec. cor. bears West, 45 lks. dist., and at 79.10 chs. fall 63 lks. E. of the cor. of secs. 25, 30, 31, and 36.

From the cor. of secs. 25, 30, 31, and 36, North retracing E. bdy. of sec. 25; at 38.57 chs. the  $\frac{1}{4}$  sec. cor. bears West, 41 lks. dist., and at 77.11 chs. fall 69 lks. E. of the cor. of secs. 19, 24, 25, and 30.

From the cor. of secs. 19, 24, 25 and 30, North retracing E. bdy. of sec. 24; at 38.15 chs. the  $\frac{1}{4}$  sec. cor. bears East, 6 lks. dist., and at 75.95 chs. fall 2 lks. W. of the cor. of secs. 13, 18, 19 and 24.

From the cor. of secs. 13, 18, 19, and 24, North retracing E. bdy. of sec. 13; at 37.58 chs. the  $\frac{1}{4}$  sec. cor. bears West, 28 lks. dist. and at 75.48 chs. fall 58 lks. E. of the cor. of secs. 7, 12, 13 and 18.

From the cor. of secs. 7, 12, 13 and 18, North retracing E. bdy. of sec. 12; at 38.20 chs. the  $\frac{1}{4}$  sec. cor. bears West, 16 lks. dist., and at 76.64 chs. fall 7 lks. E. of the cor. of secs. 1, 6, 7 and 12.

From the cor. of secs. 1, 6, 7 and 12, North retracing E. bdy. of sec. 1; at 39.18 chs. the  $\frac{1}{4}$  sec. cor. bears West, 10 lks. dist. and at 86.95 chs. fall 83 lks. E. of the closing cor. of Tps. 32 S., Rs 8 and 9 W.

-----

I return to the standard cor. of Tps. 32 S., Rs. 8 and 9 W., previously described.

Thence

N. 0°39'W., resurveying E. bdy. of sec. 36.

Descend N. slope, through heavy timber and dense undergrowth.

- 2.10 Creek, 2 lks. wide, course NW.; ascend.
- 8.35 Dry ravine, course SW.; continue ascent.
- 20.65 Top of ridge, bears NW. and SE.; descend.
- 31.75 Dry ravine, course NE.; ascend.
- 34.50 Top of spur, slopes E.; descend.
- 39.00 Dry ravine, course E.; ascend.
- 39.56 Intersect the old  $\frac{1}{4}$  sec. cor., which is a basalt stone, 5x12x7 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except for some discrepancies in the position of the bearing trees. I change this cor. to refer to sec. 31 only and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the