

Resurvey East bdy., T. 32 S., R. 9 W.

CHAINS

ground, for $\frac{1}{4}$ cor. of sec. 31, T. 32 S., R. 8 W. only,
with brass cap marked

$\frac{1}{4}$
S31
1917

from which

A Fir, 18 ins. diam., bears N.72°E., 58 lks. dist.

marked $\frac{1}{4}$ S 31 B T (Old B.T.)

A Fir, 12 ins. diam., bears S.86°E., 74 lks. dist.

marked $\frac{1}{4}$ S 31 B T (New B.T.)

Thence

N.0°16'W., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$
S36
1917

from which

A Fir, 20 ins. diam., bears S.72°W., 67 lks. dist.

marked $\frac{1}{4}$ S 36 B T.

A Fir, 8 ins. diam., bears N.35°W., 33 lks. dist.

marked $\frac{1}{4}$ S 36 B T.

42.20 Top of spur, slopes NE.; descend.
43.00 Dry ravine, course E.; ascend.
51.90 Top of spur, slopes E.; descend.
55.80 Head of ravine, course E.; ascend.
62.00 Top of ascent; over nearly level land.
65.00 Descend NE. slope.
78.50 Ravine, course E.; ascend.
79.10 Intersect the old cor. of secs. 25, 30, 31 and 36, which
is a basalt stone, 6x12x8 ins. above ground, marked and
witnessed as described by the surveyor general. I change
this cor. to refer to secs. 30 and 31, T. 32 S., R. 8 W.