

County Surveyor's Record, Douglas County, Oregon

Resurvey East Bdy., T. 32 S., R. 9 W.

CHAINS

only and perpetuate it as follows: alongside the old cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 30 and 31, T. 32 S., R. 8 W.
only, with brass cap marked

T32S
S30
S31
R8W

1917

from which

A Fir, 48 ins. diam., bears N.57°E., 65 lks. dist.
marked T 32 S R 8 W S 30 B T. (Old B.T.)

A Fir, 18 ins. diam., bears S.43°E., 87 lks. dist.
marked T 32 S R 8 W S 31 B T (Old B.T.)

Thence

N.0°36'W., continuing my measurements

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 25 and 36, with brass cap marked

T32S
S25
S36
R9W

1917

from which

A Fir, 36 ins. diam., bears S.40°W., 65 lks. dist.,
marked T 32 S R 9 W S 36 B T.

A Laurel, 14 ins. diam., bears N.15°W., 78 lks. dist.
marked T 32 S R 9 W S 25 B T.

Land, mountainous.

Soil, stony clay loam and shale rock, 3rd and 4th rate.

Timber, Fir, Sugar Pine, and Laurel.

Undergrowth, Tan Oak, Rhododendron, and Live Oak.

N.0°36'W., resurveying E. bdy. of sec. 25.

Along E. slope, through heavy timber and dense undergrowth.

3.00 Top of spur, slopes E.; descend.

14.40 Dry ravine, course NE.; ascend.