

## Resurvey East Bdy., T. 32 S., R. 9 W.

CHAINS

Timber, Fir, Sugar Pine, Laurel, and Chinquapin.

Undergrowth, Chinquapin, Tan Oak, and Live Oak.

N.0°05'E., resurveying E. bdy. of sec. 24.

Descend NE slope, through heavy timber and dense undergrowth.

4.35 Creek, 2 lks. wide, course SE.; ascend.

22.00 Top of spur, slopes E.; descend steep rocky slope.

34.36 Intersect the old  $\frac{1}{4}$  sec. cor., which is a basalt stone, 5x12x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except that the bearing trees are now dead. I change this cor. to refer to secs. 19 only and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 19, T. 32 S., R. 8 W. only with brass cap marked

$\frac{1}{4}$   
 S19  
 1917

from which

A Laurel, 10 ins. diam., bears N.59°E., 46 lks. dist.,  
 marked  $\frac{1}{4}$  S 19 B T (New B.T.)

A Fir, 8 ins. diam., bears S.89°E., 35 lks. dist.,  
 marked  $\frac{1}{4}$  S 19 B T (New B.T.)

Thence

N.0°03'W., continuing my measurements

38.90 Creek, 5 lks. wide, course E.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 24 only, with brass cap marked

$\frac{1}{4}$   
 S24  
 1917

from which

A Fir, 6 ins. diam., bears S.60°W., 42 lks. dist.  
 marked  $\frac{1}{4}$  S 24 B T.

A Fir, 24 ins. diam., bears N.22°W., 21 lks. dist.