

## County Surveyor's Record, Douglas County, Oregon

Resurvey East Bdy., T. 32 S., R. 9 W.

CHAINS

A Sugar Pine, 24 ins. diam., bears N.20\*W., 59 lks. dist., marked T 32 S R 9 W S 13 B T.

Land, mountainous.

Soil, stony clay loam and shale rock, 3rd and 4th rate.

Timber, Fir, and Sugar Pine.

Undergrowth, Chinquapin, Tan Oak, and Buckhorn.

N.0\*26\*W., resurveying E. bdy. of sec. 13.

Descend NE. slope, through scattering timber and dense undergrowth

11.65 Creek, 5 lks. wide, course E.; ascend steep slope.

28.25 Top of spur, slopes E.; descend.

29.74 Intersect the old  $\frac{1}{4}$  sec. cor., which is a decayed and partly burned post, witnessed as described by the surveyor general. I change this cor. to refer to sec. 18 only and perpetuate it as follows: alongside the old cor. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 18, T. 32 S., R. 8 W. only with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S18 \\ 1917 \end{array}$$

from which

A Fir, 48 ins. diam., bears N.71\*E., 65 lks. dist. marked  $\frac{1}{4}$  S 18 B T (Old B.T.)

A Sugar Pine, 16 ins. diam., bears S.69\*E., 97 lks. dist., marked  $\frac{1}{4}$  S 18 B T (New B.T.)

Thence

N.0\*27\*W., continuing my measurements

34.55 Creek, 1 lk. wide, course SE.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 13 only, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S13 \\ 1917 \end{array}$$

from which