


Resurveying East Bdy., T. 32 S., R. 9 W.

CHAINS

A Sugar Pine, 50 ins. diam., bears S.75\*W., 50 lks. dist., marked  $\frac{1}{4}$  S 13 B T.  
 A Fir, 36 ins. diam., bears N.30\*W., 76 lks. dist. marked  $\frac{1}{4}$  S 13 B T.

- 41.15 Top of spur, slopes E.; descend.
- 51.50 Creek, 5 lks. wide, course E.; ascend.
- 60.65 Top of spur, slopes E.; descend.
- 67.64 Intersect the old cor. of secs. 7, 12, 13 and 18, which is a basalt stone 18x12x10 ins. loosely set, marked and witnessed as described by the surveyor general, except for a discrepancy in the distance of the NE bearing tree and that the SE. tree is dead. I change this cor. to refer to secs. 7 and 18 only and perpetuate it as follows: alongside the old cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7 and 18, T. 32 S., R. 8 W. only, with brass cap marked



from which

A Fir, 36 ins. diam., bears N.80\*E., 23 lks. dist., marked T 32 S R 8 W S 7 B T. (Old B.T.)  
 A Fir, 30 ins. diam., bears S.82\*E., 57 lks. dist., marked T 32 S R 8 W S 18 B T (New B.T.)

Thence

N.0\*14'W., continuing my measurements

- 67.68 Creek, 3 lks. wide, course E.; ascend.
- 70.00 Leave timber, bears E. and W.
- 77.25 County trail, Dothan to Gold Beach, bears E. and W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins in the ground, for cor. of secs. 12 and 13, with brass cap marked