

Resurvey of East Bdy., T. 32 S., R. 9 W.

CHAINS

dist., marked  $\frac{1}{4}$  S 7 B T (New B T.)

A Fir, 5 ins. diam., bears S.26°E., 8 lks. dist.,  
marked  $\frac{1}{4}$  S 7 B T (New B T.)

Thence

N.0°08'E., continuing my measurements.

Descend NW slope.

33.25 Ravine, course NW., ascend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground, for  $\frac{1}{4}$  cor. of sec. 12 only, with brass  
cap, marked

$\frac{1}{4}$  |  
S12 |  
1917

from which

A Fir, 36 ins. diam., bears S.77°30'W., 125 lks.  
dist., marked  $\frac{1}{4}$  S 12 B T.

A Laurel, 6 ins. diam., bears N.37°W., 80 lks.  
dist., marked  $\frac{1}{4}$  S 12 B T.

47.20 Creek, 3 lks. wide, course W., ascend.

51.60 Top of spur, slopes W., descend.

64.28 Intersect the point of old cor. of Secs. 1, 6, 7, and  
12, located by reference to the bearing trees as  
described by the surveyor general, except a discrep-  
ancy in the record of the SE bearing tree. I change  
this cor. to refer to Secs. 6 and 7 only, and perpet-  
uate it as follows, at the exact cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground, for cor. of Secs. 6, 7, T. 32 S., R. 8 W.  
only, with brass cap marked

T32S  
S6  
-----  
S7  
R8W  
1917

from which