

County Surveyor's Record, Douglas County, Oregon

8861

Exteriors of T. 32 S., R. 10 W.,
as surveyed by Richmond S. Dickerson, Deputy Surveyor,
under Contract No. 474, dated May 1, 1883.

CHAINS	North, bet. Secs. 19 and 24 *****
80.00	<p>Set a stone, 18x10x6 ins., 12 ins. in the ground for the cor. to Secs. 13, 18, 19 and 24, marked with 3 notches on N and S Angles of stone and from which</p> <p>A Fir, 16 ins. diam., bears N.55*E., 58 lks. dist., marked T 32 S R 9 W S 18 B T.</p> <p>A Fir, 26 ins. diam., bears S.60*E., 53 lks. dist., marked T 32 S R 9 W S 19 B T.</p> <p>A Fir, 32 ins. Diam., bears S.51*W., 53 lks. dist., marked T 32 S R 10 W S 24 B T.</p> <p>A Fir, 40 ins. diam., bears N.15*W., 99 lks. dist., marked T 32 S R 10 W S 13 B T.</p> <p>Land, high and mountainous. Soil, 3rd rate.</p> <p>Densely covered with forest of Fir, Pine, Laurel and Chinquapin.</p> <p>Undergrowth, chiefly Laurel and Fir.</p>
	North, bet. Sec. 13 and 18.
	Va. 19*45'E.
	Ascend.
37.00	<p>Top of mountain bet. Rogue River and Umpqua waters. This point is the cor. to Douglas and Coos Co's. Mt. Bolivar bears N.78*W. Descend.</p>
40.00	<p>Set a stone, 14x12x10 ins. ^{10 ins.} in the ground for the $\frac{1}{4}$ Sec. cor. marked $\frac{1}{4}$ on West side and from which</p> <p>A Fir, 30 ins. diam., bear N.28*E., 34 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A Fir, 40 ins. in diam., bears N.42*W., 25 lks. dist., marked $\frac{1}{4}$ S B T.</p>
77.90	A Creek, 2 lks. wide, C. NE.
80.00	<p>A Fir, 30 ins. diam., which I marked T 32 S R 9 W S 7 on NE, S 18 on SE, R 10 W S 13 on S W faces and S 12 on N W, also 4 notches on S. and 2 notches on N side of same from which</p> <p>A Fir, 48 ins. in diam., bear N.62*E., 43 lks. dist., marked T 32 S R 9 W S 7 B T.</p>