

Resurvey of Portion of West Bdy. of T. 32 S., R. 9 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 13, T. 32 S., R. 10 W. only, with brass cap marked

$\frac{1}{4}$ |
S13 |
1917

from which

A Fir, 40 ins. diam., bears S.69*W., 64 lks. dist., marked $\frac{1}{4}$ S 13 B T (New B.T.)

A Fir, 30 ins. diam., bears N.60*W., 69 lks. dist., marked $\frac{1}{4}$ S 13 B T (Old B.T.)

Thence

N.0*28'E., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 18 only, with brass cap marked

$\frac{1}{4}$ |
S18 |
1917

from which

A Fir, 30 ins. diam., bears N.38*E., 31 lks. dist., marked $\frac{1}{4}$ S 18 B T.

A Fir, 36 ins. diam., bears S.78*E., 33 lks. dist., marked $\frac{1}{4}$ S 18 B T.

45.80 Ravine, course NE.

50.70 Top of rocky point, slopes NE.; descend.

53.60 Ravine, course E.

68.40 Creek, 4 lks. wide, course NW.; ascend.

71.00 Top of ascent; descend NW. slope.

71.99 Intersect the old cor. of secs. 7, 12, 13, and 18, which is a basalt stone, 18x10x12 ins., loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 12 and 13 only and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 12 and 13, T. 32 S., R. 10 W.