

13

Resurvey of Portion of West Bdy. of T. 32 S., R. 9 W.

CHAINS

- 44.30 Creek, 1 lk. wide, course SW.
- 50.00 A rock, 15x15x15 ft. above ground, bears West, 15 lks. dist.,
- 52.55 Creek, 1 lk. wide, course W.; ascend.
- 53.85 Ravine, course SW.

70.56 Intersect the old cor. of secs. 1, 6, 7 and 12, which is a basalt stone, 15x12x5 ins., loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 1 and 12 only and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1 and 12, T. 32 S., R. 10 W. only, with brass cap marked

T32S
S1
S12
R10W
1917

from which

A Fir, 30 ins. diam., bears S.11*W., 85 lks. dist., marked T 32 S R 10 W S 12 B T (Old B.T.)

A Fir, 40 ins. diam., bears N.34*W., 19 lks. dist., marked T 32 S R 10 W S 1 B T (Old B.T.)

Thence

N.0*38'W., continuing my measurements

- 79.80 Trail, bears E. and W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 6 and 7, with brass cap marked

T32S
S6
S7
R9W
1917

from which

A Fir, 30 ins. diam., bears N.84*E., 34 lks. dist., marked T 32 S R 9 W S 6 B T.

A Fir, 48 ins. diam., bears S.14*E., 59 lks. dist., marked T 32 S R 9 W S 7 B T.