

15

Resurvey of West Bdy., T. 32 S., R. 9 W.

CHAINS

from which

A fir, 24 ins. diam., bears N.53*E., 18 lks. dist.,
marked $\frac{1}{2}$ S 6 B T.

A fir, 9 ins. diam., bears S.44*E., 39 lks. dist.,
marked $\frac{1}{2}$ S 6 B T.

42.70 Top of rocky spur, slopes E.; continue ascent.

52.40 Top of ridge, bears NE. and SW.; along steep W. slope.

68.08 Intersect the closing cor. of Tps. 32 S., Rs. 9 and 10 W.,
previously described.

Land, mountainous.

Soil, stony clay loam and shale rock, 3rd and 4th rate.

Timber, fir, sugarpine, cedar, hemlock and live oak.

Undergrowth, live oak, tan oak and snowbrush.

Subdivisions, T. 32 S., R. 9 W.
Same Deputies and Contract.

Note:

As the S. bdy. of sec. 36 is within 10' of the cardinal
I commence at the standard cor. of secs. 35 and 36 and run
North on a Sectional Guide Meridian bet. secs. 35-36,
25-26, 23-24, 13-14 and 11-12. I then commence at the cor.
of secs. 25, 26, 35 and 36 and run West on a Sectional
Correctional Line bet. secs. 26-35, 27-34, 28-33, 29-32 and
30-31.

From the standard cor. of secs. 35 and 36, on the S. bdy.
of the Tp.

North, on a Sectional Guide Meridian, bet. secs. 35 and 36.

Over mountainous land, through heavy timber and dense
undergrowth.

0.50 Creek, 2 lks. wide, course SE.; ascend brushy slope.

1.00 Leave timber, bears E. and W.

31.00 Top of high ridge, bears E. and W.; descend.

Enter heavy timber, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{2}$ sec. cor., with brass cap marked