

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 32 S., R. 9 W.

16

CHAINS

1/4
S35|S36
1917

from which

A fir, 24 ins. diam., bears S.33*E., 16 lks. dist.,
marked 1/4 S 36 B T.

A sugar pine, 50 ins. diam. bears N.21*W., 48 lks.
dist., marked 1/4 S 35 B T.

- 41.90 Ravine, course NW.; ascend.
- 48.75 Top of spur, slopes NW.; descend.
- 55.30 Creek, 2 lks. wide, course NW.; ascend.
- 59.65 Ravine, course SW.
- 63.50 Leave timber, bears E. and W.
- 69.40 Top of high spur, slopes NW.; descend steep slope.
Enter heavy timber, bears NW. and SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 25, 26, 35, and 36, with brass
cap marked

T32S|R9W
S26|S25
S35|S36
1917

from which

A fir, 20 ins. diam., bears N.58*E., 28 lks. dist.,
marked T 32 S R 9 W S 25 B T.

A fir, 40 ins. diam., bears S.40*E., 46 lks. dist.,
marked T 32 S R 9 W S 36 B T.

A fir, 36 ins. diam., bears S.27*W., 73 lks. dist.,
marked T 32 S R 9 W S 35 B T.

A fir, 30 ins. diam., bears N. 74*W., 18 lks. dist.,
marked T 32 S R 9 W S 26 B T.

Land, mountainous.

Soil, shale and broken rock, 4th rate.

Timber, fir and sugar pine.

Undergrowth, chinquapin, tan oak, buckhorn, rhododendron
and laurel.