

Subdivisions, T. 32 S., R. 9 W.

CHAINS

North, on a Sectional Guide Meridian, bet. secs. 23 and 24.

Ascend through heavy timber and dense undergrowth.

8.15 Top of ridge, bears NE, and SW.; descend.

15.50 Ravine, course W.

17.85 Top of spur, slopes W.

21.65 Ravine, course W.

31.55 Creek, 2 lks. wide, course SW.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec cor., with brass cap marked

1/4
S23/S24
1917

from which

A fir, 48 ins. diam., bears S.67*E., 50 lks. dist., marked 1/4 S 24 B T.

A fir, 48 ins. diam., bears N.57*W., 128 lks. dist., marked 1/4 S 23 B T.

40.50 Top of spur, slopes NW.; descend.

55.50 Creek, 2 lks. wide, course SW.; ascend.

72.40 Top of spur, slopes SW.; descend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap marked

T32S, R9W
S14 | S13

S23 | S24
1917

from which

A fir, 36 ins. diam., bears N.8*E., 127 lks. dist., marked T 32 S R 9 W S 13 B T.

A fir, 36 ins. diam., bears S.78*E., 127 lks. dist., marked T 32 S R 9 W S 24 B T.

A fir, 48 ins. diam., bears S.44*30*W., 239 lks. dist., marked T 32 S R 9 W S 23 B T.

A fir, 30 ins. diam., bears N.51*W., 122 lks. dist., marked T 32 S R 9 W S 14 B T.