

Subdivisions, T. 32 S., R. 9 W.

CHAINS	North, on a random line, bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
70.63	Intersect the N. bdy. of the Tp., 4 lks. E. of the cor. of secs. 1 and 2.
	Thence
	S.0*02'E., on a true line, bet. secs. 1 and 2.
	Ascend through scattering timber and dense undergrowth.
4.00	Ravine in bedrock, course NE.; continue ascent.
20.40	Top of spur, slopes NE.; along E. slope.
25.80	Ravine, course E.
30.63	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S2 S1 1917
	from which
	A sugar pine, 24 ins. diam., bears S.18'E., 116 lks. dist., marked $\frac{1}{4}$ S 1 B T.
	A laurel, 9 ins. diam., bears S.10*30'W., 91 lks. dist., marked $\frac{1}{4}$ S 2 B T.
40.65	Enter heavy timber, bears E. and W.
53.00	Leave heavy timber, bears E. and W.
70.63	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous.
	Soil, clay loam, gravelly in places, 2nd and 3rd rate.
	Timber, fir, tan oak, laurel and chinquapin.
	Undergrowth, laurel and tan oak.
	From the cor. of secs. 25, 26, 35 and 36.
	West, on a Sectional Correction Line, bet. secs. 26 and 35.
	Ascend through heavy timber and dense undergrowth.
3.00	Top of spur, slopes N.; descend.
17.00	Ravine, course N.; ascend.
22.30	Top of spur, slopes NE.; descend steep slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked