

Subdivisions, T. 32 S., R. 9 W.

CHAINS	
	S.89°50'W., on a true line, bet. secs. 23 and 26. Ascend through heavy timber and dense undergrowth.
5.00	Top of ridge, bears NE. and SW.; descend.
10.50	Ravine, course NW.; ascend.
12.40	Top of spur, slopes NW.; descend.
14.00	Ravine, course NW.; ascend.
29.00	Top of spur, slopes NW.; descend.
39.92	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{l} S23 \\ S26 \\ 1917 \end{array}$ from which A fir, 14 ins. diam., bears S.65°E., 10 lks. dist., marked $\frac{1}{4}$ S 26 B T. A fir, 6 ins. diam., bears N.19°30'W., 27 lks. dist., marked $\frac{1}{4}$ S 23 B T.
41.90	Ravine, course NW.; along N. slope.
47.60	Top of spur, slopes NS.; descend steep slope.
69.10	Kelsey Creek, 10 lks. wide, course SW.; ascend SE. slope.
79.84	The cor. of secs. 22, 23, 26 and 28. Land, mountainous. Soil, stony clay, 2nd and 3rd rate. Timber, fir, sugar pine, cedar and laurel. Undergrowth, tan oak, chinquapin and laurel.
	N.0°01'W., bet. secs. 22 and 23. Ascend through heavy timber and dense undergrowth.
1.30	Creek, 1 lk. wide, course E.; continue ascent.
3.55	Creek, 1 lk. wide, course E.; continue ascent.
8.50	Top of spur, slopes SE.; descend.
10.70	Creek, 1 lk. wide, course SE.; continue descent.
22.15	Creek, 2 lks. wide, course SE.; ascend. Leave heavy; enter scattering timber, bears NW. and SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{l} S22 \\ S23 \\ 1917 \end{array}$