

County Surveyor's Record, Douglas County, Oregon

40

Subdivisions of T. 32 S., R. 9 W.

CHAINS

T32S, R9W	
S9	S10
<hr/>	
S16	S15
1917	

from which

A fir, 36 ins. diam., bears N.14*E., 264 lks. dist.,
marked T 32 S R 9 W S 10 B T.

A fir, 40 ins. diam., bears S.44*E., 54 lks. dist.,
marked T 32 S R 9 W S 15 B T.

A fir, 36 ins. diam., bears S.7*W., 108 lks. dist.,
marked T 32 S R 9 W S 16 B T.

A fir, 16 ins. diam., bears N.48*W., 249 lks. dist.,
marked T 32 S R 9 W S 9 B T.

Land, mountainous.

Soil, stony clay, 3rd rate.

Timber, fir, sugar pine and cedar.

Undergrowth, tan oak, buckhorn, rhododendron and chinquapin.

N.89*50'E., on a random line, bet. secs. 10 and 15.

40.00 Set temp. $\frac{1}{4}$ sec. cor.79.94 Intersect the N. and S. line, 19 lks. N. of the cor. of
secs. 10, 11, 14 and 15.

Thence

S.89*58'W., on a true line, bet. secs. 10 and 15.

Ascend through heavy timber and dense undergrowth.

12.00 Top of high spur, slopes NE.; descend steep rocky slope.

29.00 Creek, 6 lks. wide, course NE.; ascend.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	S10
	S15
	1917

from which

A fir, 8 ins. diam., bears N. 65*E., 51 lks. dist.,
marked $\frac{1}{4}$ S 10 B T.

A sugar pine, 8 ins. diam., bears S.81*W., 56 lks.
dist., marked $\frac{1}{4}$ S 15 B T.