

41

Subdivisions of T. 32 S., R. 9 W.

CHAINS

- 44.00 Ravine, course SE.; continue ascent.
- 59.80 Creek, 1 lk. wide, course SE.; ascend along S. side of creek.
- 67.35 Same creek, course NE.; ascend along N. side of creek.
- 69.00 Same creek, course SE.; ascend.
- 79.94 The cor. of secs. 9, 10, 15 and 16.

Land, mountainous.

Soil, rocky clay loam, 3rd and 4th rate.

Timber, fir; sugar pine, cedar and laurel.

Undergrowth, tan oak, laurel, live oak and young fir.

N.0*02'W., bet. secs. 9 and 10.

Ascend gradual slope, through scattering timber and dense undergrowth,

- 8.75 Top of ridge, bears NE. and SW.; descend.

Trail, Camas Valley to Rogue River, bears NE. and SW.

- 18.10 Spring, drains NW.

- 26.00 Enter heavy timber, bears E. and W.

- 37.00 Top of spur, slopes NW.; descend.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S9 | S10
 1917

from which

A yew, 7 ins. diam., bears N.30*E., 20 lks. dist., marked $\frac{1}{4}$ S 10 B T.

A chinquapin, 12 ins. diam., bears N.87*W., 27 lks. dist., marked $\frac{1}{4}$ S 9 B T.

- 57.90 Creek, 3 lks. wide, course NW.; ascend.

- 65.80 Top of spur, slopes NW.; descend.

- 72.60 Top of spur, slopes NW.; along W. slope.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T32S R9W
 S4 | S3
 S9 | S10
 1917