

County Surveyor's Record, Douglas County, Oregon

46

Subdivisions of T. 32 S., R. 9 W.

CHAINS

A cedar, 30 ins. diam., bears N.85*W., 3 lks. dist.,
marked $\frac{1}{4}$ S 17 B T.

48.05 Creek, 2 lks. wide, course SW.; ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 8, 9, 16 and 17, with brass
cap marked

T32S R9W	
SS	S9
S17	S16
1917	

from which

A fir, 30 ins. diam., bears N.30*E., 91 lks. dist.,
marked T 32 S R 9 W S 9 B T.

A fir, 40 ins. diam., bears S.63*E., 10 lks. dist.,
marked T 32 S R 9 W S 16 B T.

A fir, 40 ins. diam., bears S.52*W., 41 lks. dist.,
marked T 32 S R 9 W S 17 B T.

A fir, 48 ins. diam., bears N.11*W., 35 lks. dist.,
marked T 32 S R 9 W S 8 B T.

Land, mountainous.

Soil, gravelly clay loam, 2nd rate.

Timber, cedar, chinquapin and live oak.

Undergrowth, rhododendron, tan oak, hazel and fir.

N.89*45'E., on a random line, bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.74 Intersect the N. and S. line, 42 lks. N. of the cor. of
secs. 9, 10, 15 and 16.

Thence

N.89*57'W., on a true line, bet. secs. 9 and 16.

Ascend E. slope, through burn.

4.25 Top of ridge, bears NE. and SW.; old trail, Camas Valley
to Rogue River, bears NE. and SW.; along N. slope.

11.00 Top of spur, slopes NW.

Leave burn; enter timber, bears NE. and SW.

18.75 Creek, 2 lks. wide, course N.